


TECHNICAL DATA SHEET

	TDS No:	040	Issue No:	1
	Issue Date:		14/10/14	
	Revision Date:		14/07/16	
	Page No:		1 of 1	
PRODUCT	NovaMask 80 Low Bake Masking Tape			

NovaMask 80 Low Bake is a creped general purpose masking tape, with a solvent rubber pressure sensitive adhesive that offers clean removal after bake cycles up to 80°C.

Also suited to a wide variety of general internal painting, packaging, bundling and sealing applications, the crepe backing is conformable around sharp corners and the hot melt adhesive gives immediate adhesion resisting lift or curl.

Technical Data

Parameter	Specification
Backing	Crepe Paper
Colour	Natural
Adhesive	Solvent Rubber
Thickness	0.127mm
Temperature Range	10 - 82°C
Adhesion to Steel	9.8N/25mm
Quick Stick to Steel	3.3N/25mm
Tensile strength	40N/25mm
Elongation	6.4%
Shelf Life	12 Months
Dimensions	25mm x 50m (48/carton) 50mm x 50m (24/carton)

Please contact us at enquiries@innovasolutions.co.uk for further information.

Innova Solutions: bonding people, fixing problems: +44 (0)1282 867 390

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.