


TECHNICAL DATA SHEET			
	TDS No:	064	Issue No: 1
	Issue Date:	15/05/15	
	Revision Date:	15/05/16	
	Page No:	1 of 1	
PRODUCT		Tamper Evident Security Tape	

Description

Tamper evident security tape leaves a very obvious 'opened void' message in the tape itself and on the surface underneath when removed.

Suitable as a deterrent for potential thefts or fraud with the bright red colour and distinctive print.

Ideally suited for packaging valuable or confidential items in storage or transit, giving reassurance to the receiver that contents have not been tampered with.

Features

- For securely sealing boxes and film-wrapped pallets.
- Permanent void message appears when peeling the tape from surface.
- Trace performance 95% minimum.
- Available in red and blue designs,
- Exclusive 'Security Tape' surface designs on standard red and blue type.
- Suitable for paper materials and cardboard, pallet stretch film and shrink-wrap.

Properties

Property	Parameter
Construction	Printed polyester film
Adhesive Type	Pressure Sensitive Acrylic resin
Colour	Red & Blue
Application Temperature Range	-15°C to 25 ⁰ C
Temperature Resistance	-40°C to 80 ⁰ C
Backing Thickness	0.025mm
Total Thickness	0.08mm
Initial Tack(PSTC-6 #14 ball)	<10cm
Holding Power (PSTC-7)	>24hrs : 0.5Kg/25mm x 25mm
90 ⁰ C peel Adhesion for VOID	g/25mm = 20-100 (N/25mm =<0.2 – 1.0)
Dimensions	50mm Wide x 50m Length

Application

Best applied at room temperature on a clean surface

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.