


TECHNICAL DATA SHEET

| | | | | |
|---|-----------------------|-----|-----------|---|
|  | TDS No: | 053 | Issue No: | 1 |
| | Issue Date: | | 20/02/15 | |
| | Revision Date: | | 14/07/16 | |
| | Page No: | | 1 of 1 | |
| PRODUCT | NovaFelt Black | | | |

Description

NovaFelt Black is a very versatile Needle Loom self-adhesive backed felt that can be used in a wide variety of applications, including:

- Surface protector for glass and other materials
- Weather strips for windows
- Flooring protection
- Anti-vibration/Sound absorption
- Sealing
- Automotive & Caravan interiors
- Transport racking
- Cushioning

Specifications

Felt:

| Property | Value |
|-------------------|-------------------------|
| Type | Unsupported Needle Loom |
| Colour | Black |
| Composition | 100% Polyester |
| Weight | 180 g/m ² |
| Thickness | 3mm (+/- 20%) |
| Temperature Range | from -40 °C to +150 °C |
| Reaction to Flame | Passes FMVSS302 |

Adhesive:

| Property | Value |
|--|---|
| Support | Non-woven, 12 g/m ² |
| Type | a modified polyacrylate |
| Interliner | Release paper, yellow, 90 g/ m ² |
| Adhesive weight | 90 g/m ² |
| Total thickness | 0.10 mm |
| Temperature resistance (according to the ATP test method AA-B-12-07) | from -40 °C to +90 °C |
| Adhesive strength (according to AFERA 5001) | Min 21 N/25 mm (Contact time: 1 hr.) |

NovaFelt Black is available in 20mm width x 3mm thickness x 13.5m roll length.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.